



Please type a plus sign (+) inside this box → 

PTO/SB/05 (12/97)
Approved for use through 09/30/2000. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))		Attorney Docket No.	ISM/007	Total Pages	63
		First Named Inventor or Application Identifier			
		ADNAN SHENNIB			
		Express Mail Label No.	EK 034 390 353 US		
APPLICATION ELEMENTS <i>See MPEP chapter 600 concerning utility patent application contents.</i>		ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231			
<p>1. <input checked="" type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing)</p> <p>2. <input checked="" type="checkbox"/> Specification [Total Pages <u>42</u>] (preferred arrangement set forth below) - Descriptive title of the invention - Cross References to Related Applications - Statement Regarding Fed sponsored R&D - Reference to Microfiche Appendix - Background of the Invention - Brief Summary of the Invention - Brief Description of the Drawings (if filed) - Detailed Description - Claim(s) - Abstract of the Disclosure</p> <p>3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) [Total Sheets <u>9</u>]</p> <p>4. <input checked="" type="checkbox"/> Oath or Declaration [Total Pages <u>2</u>] a. <input checked="" type="checkbox"/> Newly executed (original or copy) b. <input type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) [Note Box 5 below] i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).</p> <p>5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference herein.</p>		<p>6. <input type="checkbox"/> Microfiche Computer Program (Appendix)</p> <p>7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) a. <input type="checkbox"/> Computer Readable Copy b. <input type="checkbox"/> Paper Copy (identical to computer copy) c. <input type="checkbox"/> Statement verifying identity or above copy</p>			
		ACCOMPANYING APPLICATION PARTS <p>8. <input checked="" type="checkbox"/> Assignment Paper (cover sheet & document(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement <input checked="" type="checkbox"/> Power of Attorney (when there is an assignee) 10. <input type="checkbox"/> English Translation Document (if applicable) 11. <input type="checkbox"/> Information Disclosure <input type="checkbox"/> Copies of IDS Statement (IDS)/PTO-1449 Citations 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (should be specifically itemized) 14. <input checked="" type="checkbox"/> Small Entity <input type="checkbox"/> Statement filed in prior application, Statement(s) Status still proper and desired 15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 16. <input checked="" type="checkbox"/> Other: Cover Sheet..... Check to Commissioner for \$1,299.00...</p>			
17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information: <input type="checkbox"/> Continuation <input type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No.: _____					
18. CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number or Bar Code Label or <input checked="" type="checkbox"/> Correspondence address below (insert Customer No. or Attach bar code label here)					
NAME	Donald R. Greene 				
	Registration No. 22470 Date: September 21, 1999				
ADDRESS	Post Office Box 12995				
CITY	Scottsdale	STATE	AZ	ZIP CODE	85267-2995
COUNTRY	US	TELEPHONE	(480) 488-9895	FACSIMILE	(480) 488-5654

jc566 U.S. PTO
09/21/99
09/400151
09/21/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

ADNAN SHENNIB

Group Art Unit: _____

Serial No. (to be assigned)

Examiner: _____

Filed: Herewith


Title: PERSONAL HEARING EVALUATOR

NEW APPLICATION TRANSMITTAL

1. This new application is for an original utility patent, consisting of 42 pages of specification, including 18 pages of claims (109 claims) and a 1 page abstract, plus a cover sheet and 9 sheets (13 Figures) of informal drawings. Also enclosed is the PTO Application Transmittal Form (PTO/SB/05).
2. The application also includes a Combined Declaration and Power of Attorney, and Assignment, both, executed by the inventor, with Assignment recordation form.
3. Also enclosed herewith are a Verified Statement Claiming Small Entity Status executed by the assignee, and a separate Verified Statement Claiming Small Entity Status executed by the inventor. The filing fee has therefore been calculated on a small entity basis, as follows:

CLAIMS AS FILED				CALCULATION	
				(Small Entity)	
	Number Filed		Number Extra	Rate	Basic Fee
					\$380.00
Total Claims	109	- 20 =	89	x \$ 9.00	= 801.00
Independent Claims	5	- 3 =	2	x \$39.00	= <u>78.00</u>
Filing Fee, Total					\$1,259.00

4. Enclosed herewith is a check to the Commissioner in the amount of \$1,299.00 to cover both the above filing fee and the \$40.00 fee for recordation of the enclosed Assignment.


Donald R. Greene, Reg. No. 22470
Post Office Box 12995
Scottsdale, AZ 85267-2995
(480) 488-9895

Dated: 09/21/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: :
: :
ADNAN SHENNIB : Group Art Unit: _____
: :
Serial No. (to be assigned) : Examiner: _____
: :
Filed: Herewith :

Title: PERSONAL HEARING EVALUATOR

EXPRESS MAIL CERTIFICATE


Express Mail Label No. **EK 034 390 353 US**

Date of Deposit: September 21, 1999

I hereby certify that the following attached papers:

- (1) Application including cover sheet; specification (42 pages) incl claims (18 pages, 109 claims) and Abstract (1 page); and informal drawings (9 sheets, 13 Figures);
- (2) Combined Declaration/Power of Attorney (executed 09/20/99 by inventor);
- (3) Assignment (executed 09/20/99 by inventor), and Recordation Form therefor;
- (4) Verified Statement Claiming Small Entity Status (executed 09/20/99 by assignee);
- (5) Verified Statement Claiming Small Entity Status (executed 09/20/99 by inventor);
- (6) Application Transmittal Letters (Standard, including calculation of filing fee (small entity) and assignment recordation fee, and PTO Form PTO/SB/05);
- (7) Check payable to the Commissioner in the amount of \$1,299.00; and
- (8) Postcard (stamped, addressed) for PTO acknowledgment of receipt.

are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above, addressed to the Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.



Donald R. Greene
P.O. Box 12995
Scottsdale, AZ 85267-2995
Tel: (602) 488-9895

In re Application of: _____

 ADNAN SHENNIB : Group Art Unit: _____

 Serial No. (to be assigned) : Examiner: _____

 Filed: Herewith : _____

 Title: PERSONAL HEARING EVALUATOR

As the below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 35 United States Code, to the U.S. Patent and Trademark Office (PTO) with regard to the invention described in the above-captioned specification filed in the PTO herewith.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed or licensed or am under an obligation under contract or law to assign, grant, convey or license any rights in the invention is listed below*:

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

- **INSONUS MEDICAL, INC.**, a California corporation, having an office in Hayward, California (Verified Statement of Small Entity Status filed herewith).

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which

status as a small entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF INDEPENDENT INVENTOR: Adnan Shennib

ADDRESS: 34337 Xanadu Terrace
Freemont, California 94555

Signature: Adnan Shennib

Date: 9/20/99

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: :
:
ADNAN SHENNIB : Group Art Unit: _____
:
Serial No. (to be assigned) : Examiner: _____
:
Filed: Herewith :

Title: PERSONAL HEARING EVALUATOR

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) and 1.27(c))--SMALL BUSINESS CONCERN**

Commissioner of Patents and Trademarks
Washington, D.C. 20231

I hereby declare that I am an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF CONCERN InSonus Medical, Inc.
ADDRESS OF CONCERN 2506-B Technology Drive
Hayward, CA 94545

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.3-18, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees under Section 41 (a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full time, part time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law in the above-captioned application and in the invention disclosed therein have been conveyed by the inventor named as the applicant therein, to the small business concern identified above and remain therewith.

The rights held by the above identified small business concern are exclusive, and no rights to the invention are held by any other person or by any other concern, except for certain rights granted to the named inventor under that certain Commercialization Rights Agreement effective March 1998 between the above identified small business concern and the named inventor. I declare that the above identified small business concern has not assigned, granted, conveyed, or licensed, and is under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person or entity that could not be classified as a small entity under 37 C.F.R. 1.9(f).

I acknowledge the duty to file, in this application for patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small business entity is no longer appropriate. (37 CFR 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING

TITLE OF PERSON OTHER THAN OWNER

ADDRESS OF PERSON SIGNING

Adnan Shennib

President and CEO

InSonus Medical, Inc.

2506-B Technology Drive

Hayward, CA 94545

Signature

Adnan Shennib

Date

9/20/99

DRG/ISMSLEN 007/09209

EXPRESS MAIL LABEL NO. EK 034 390 353 US
ATTORNEY'S DOCKET: ISM/007

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES PATENT

Title: **PERSONAL HEARING EVALUATOR**

Inventor: **ADNAN SHENNIB**
Fremont, California

Assignee: **INSONUS MEDICAL, INC.**
Hayward, California

651250-1600000

PERSONAL HEARING EVALUATOR

Background of the Invention

A. Technical Field

The present invention relates generally to air-conduction hearing evaluation, and more particularly, to portable hand-held hearing testing and hearing aid fitting.

B. Description of the Prior Art

Air-conduction hearing evaluation involves the presentation of airborne sounds (test stimuli) to the ears of a test subject. The evaluation may involve threshold measurements whereby the threshold of hearing is determined at various frequencies, or suprathreshold measurements whereby loudness perceptions above threshold are determined. Suprathreshold testing include *most comfortable loudness* (MCL), *uncomfortable loudness* (UCL) and dynamic range measurements. A variety of test stimuli types are employed in audiological testing including pure tones, speech, and a variety of noise-based signals.

Test stimuli in air-conduction testing are emitted from a speaker to travel in air and ultimately reaching the eardrum. A speaker is typically positioned directly on or within the ear as in the case of circumaural earphones (headphones) and insert earphones. Alternatively, in sound field testing, a speaker is placed at a distance from the ear of the test subject in a test room (See American National Standard, specification for Audiometry, ANSI S3.6 -1996).

Sound field evaluation generally involves bulky instrumentation, complex calibration procedures and require specialized test rooms. Furthermore, precise positioning of the subject

with respect to a speaker is necessary in order to minimize errors in the intensity level of the sound at the ear. These errors are also caused by reverberations commonly found in test rooms (see Sandlin, R, Handbook of Hearing and Amplification, Ch. 6. pp 147-164, Singular Publishing group, 1995). Figs. 6-3 of Sandlin, for example, demonstrate how large the variability of pure tone sound field measurement can be for small changes in distance between the subject and the speaker.

In standard sound field audiometry, the subject is typically placed approximately at 1 meter (m) from the speaker. Unfortunately, the reverberant component of sound at 1 millimeter (mm) is significant as shown in Figs. 6-2 of Sandlin. The use of anechoic test rooms to eliminate reverberant sounds is extremely expensive and thus not employed in standard audiological test setups.

To minimize the effect of reverberant sounds, the subject should be positioned within the *direct field* of sound, which is typically within 70 centimeters (cm) from speaker. This causes the direct sound in the *direct field* to be dominant with respect to reverberant sound reflected from nearby objects in the room (i.e., walls, ceiling, floor, equipment, etc.). However, maintaining a precise seating arrangement within 70 cm of a speaker presents many challenges related to subject movement, discomfort, and even claustrophobia.

The utilization of probe tube microphone system to calibrate and regulate presentation levels has been widely used for various hearing evaluations (for example, see pp. 192- 204 in Sandlin). However, probe tube microphone instrumentation requires careful positioning of the probe tube for each hearing evaluation step performed. Furthermore, the use of microphone

probe tube systems adds considerable cost and complexity for the evaluation procedure, not to mention the inconvenience of attaching and maintaining a probe tube and its cabling for both the subject and the clinician.

In headphone audiometry (TDH-39 type for example), the distance between the test ear and the speaker is relatively stable thus alleviating the problem of speaker-subject positioning encountered in sound field audiometry. However, the headphone must be fitted in a sealing manner in order to minimize errors due to sound leakages that may occur at the headphone-ear contact area. Insert earphones (ER-3A type for example) also require a good sealing fit when inserted within the ear canal. Headphone and insert earphones can be uncomfortable and cumbersome for many individuals. Furthermore, headphone and insert earphones are particularly problematic for aided evaluation (with a hearing aid placed in the ear) because they generally interfere, physically and acoustically, with the proper function of a worn hearing device. Therefore, headphone and insert earphones are generally excluded from aided evaluation. Other problems associated with headphones and insert earphones include inaccuracies due to individual ear size variability and cabling interference and damage.

Portable and hand-held hearing evaluation is advantageous for conducting hearing testing outside the standard calibrated audiological setups. However, due to the relatively large errors associated with outside room acoustics, calibration, speaker-subject positioning and ambient background noise, portable and hand-held instruments tend to be limited to basic screening evaluation, requiring follow up testing in a proper audiological setup.

Review of state-of the-art in related hearing device technology

Heller, J., in United States patent Number (USPN) 4,567,881 describes a combination otoscope and audiometer for performing audiometric testing during otoscopic examination. Since the testing is performed while the tip of the otoscope is inserted in the ear canal, it is obviously not intended for aided evaluation whereby a hearing aid is worn in the ear canal. Furthermore, an otoscope is intended for use by a professional thus not suitable as a personal hearing evaluator.

Shennib, A. in USPN 5,197,332 describes a headset hearing tester which is worn on the head for positioning a speaker portion directly on the ear. As previously observed, headphone type audiometry not only interferes with the proper function of most hearing aids when worn, but is also bulky and uncomfortable for many users.

Chojar in USPN 5,081,441 discloses a hand-held tone generator for generating an audible tone as a test for equalizing binaural hearing aids. Chojar's device is limited to producing a single tone at single level, thus clearly not suitable for performing audiometric measurements. In fact, it is merely concerned with ensuring a balanced binaural aided hearing.

Downs, M., in USPN 5,291, 785 describe a hand-held portable device for testing infants for hearing defects. The device produces a low intensity sound for eliciting a response and a high intensity sound for eliciting reflex from the infant. Although designed to produce multi-level acoustic stimuli, the device is essentially a screening device for infants, thus not concerned with presenting accurate stimulus levels at multiple frequencies, nor concerned with aided evaluation. Furthermore, the device is clearly not designed for self-testing.

Posen et. al., in USPN 5,732,396 disclose a hand-held screening device for generating various acoustic stimuli at a distance set by a physical spacer incorporated into the screening device. The spacer makes direct contact with the ear area for positioning the speaker at 1 1/2 to 2 1/4 inches from the ear. The screening device, with a spacer incorporated within, has the advantage of providing a predetermined distance between the speaker and the test ear. However, the direct contact of the device to the ear area is not only awkward for audiometric testing, but is also difficult to operate by an individual of limited dexterity in self-testing scenarios. Furthermore, testing involving both ears simultaneously (binaural mode) is not possible with such a device.

There are numerous situations whereby it is desirable to provide a hand-held hearing evaluator with accurate multi-level test sounds. It is also desirable to provide a miniature instrument with means for self-administered testing without resorting to an expensive test performed by a hearing professional. In another situation, it is desirable to have a personal hearing evaluator to regularly verify the function of a worn hearing device. This is important since hearing aids are notorious for being subject to frequent damage and deterioration.

Therefore, it is a principal objective of the present invention to provide a hand-held hearing evaluation device for presenting multi-level and multi-frequency stimuli.

Another objective is to provide contactless means to properly position a speaker with respect to a test individual for accurate presentation of test stimuli.

A further objective is to provide a hearing evaluation device with means to automatically calibrate the level of acoustic stimuli presented.

A further objective is to provide an easy to use hand-held hearing evaluator suitable for self-administration by a test subject in either aided or unaided conditions.

Summary of the Invention

The invention provides a hand-held device comprising an audio transducer (i.e., speaker) for presenting acoustic test stimuli to a test subject within the direct sound field range of the device. The device delivers accurate multi-level and multi-frequency test stimuli for subjective response by the test subject holding the device. The battery-operated device is suitable for various hearing evaluation modes including aided (i.e., with a hearing aid worn) and unaided conditions.

In a preferred embodiment, the invention comprises an ultrasonic position sensor for measuring the position of the device with respect to the head of the test subject holding the hand held device. The distance is computed by measuring the latent period between the transmitted ultrasonic signal and the measured ultrasonic response reflected by the head or the ear. The acoustic test stimuli produced by the speaker are controlled and regulated based on the position of the device with respect to the test individual. Thus, the accurate levels of test stimuli are presented only upon the proper positioning of the device and irrespective of the exact position of the device. This eliminates position and movement-related errors commonly experienced in conventional sound field audiometry. Furthermore, the test subject or a test operator is automatically alerted whenever the device is incorrectly positioned during a test.

In an embodiment of the invention, the hand-held device is connected to an auxiliary

instrument (e.g., a computer or a microprocessor-based audiometer) for remotely controlling the device and for registering audible responses via a response switch provided on the invented device. In such embodiments, a test operator can select an acoustic test stimulus from a broader range of test stimuli. Thus, various threshold and supra-threshold tests are presented and responses are automatically registered by the auxiliary instrument.

In the preferred embodiment, the hand-held device is provided with at least two keys for selecting and presenting at least two stimulus levels. For example, the two keys may be an "S" key for presenting *Soft* level sound and a "C" key for presenting *Comfortable* level sound. The keys can be used by a test subject to routinely check the proper function of an in-situ (worn in the ear) hearing device. In another stand-alone embodiment, the hand-held device is used as an audiometric tool to assess hearing ability and specifically the need for a hearing aid use.

In the preferred embodiment, the device also provides switches for selecting one of at least two signal types such as *Noise* and *Speech* signals, and for selecting at least two frequency bands such as *Low* and *High* frequency bands. The combination of switches and key selections leads to a broad yet manageable range of test options, such as *Soft* level *High frequency Speech* or *Comfortable* level *Low* frequency *Noise*.

The device may be designed and configured for dual mode configurations by first being connected to an auxiliary instrument for performing relatively complex aided and unaided audiometric evaluation in the presence of a hearing professional, and subsequently as a personal evaluator for simple verification of hearing acuity and hearing aid function.

5 The device may be used for either binaural or monaural hearing evaluations. In binaural tests, the speaker of the device is oriented facing the forehead at a distance between 30-60 cm, depending on the individual's arm length. Although miniature and employing a miniature audio transducer, the device can produce high relatively intensity levels reaching 90 decibels (dB) sound pressure level (SPL) and more when positioned close to an ear (i.e., within few centimeters) in a monaural test mode.

Brief Description of the Drawings

10 The above and other objectives, features, aspects and attendant advantages of the invention will become further apparent from a consideration of the following detailed description of the presently contemplated best mode of practicing the invention, with reference to certain preferred embodiments and methods thereof, in conjunction with the accompanying drawings, in which:

15 **Fig. 1** is a view of a preferred embodiment of the invention showing a hand held hearing evaluation device containing a speaker and position sensor system, both oriented towards the head of the user;

Fig. 2 is a more detailed perspective view of the hearing evaluation device of **Fig. 1** being held in hand by a user;

Fig. 3 is a view of a dual-transducer position sensor for the embodiment of **Fig. 1**, having a transmitting ultrasonic transducer and a reception ultrasonic transducer;

20 **Fig. 4** is a view of a single-transducer position sensor which is preferred for the

embodiment of **Fig. 1**, having a unitary transducer for both transmitting and reception of ultrasonic signals;

Fig. 5 is a block diagram of the major components within the presently preferred embodiment of the hearing evaluation device;

5 **Fig. 6** is a view of the hearing evaluation device correctly positioned in range at 0° degree incidence angle with respect to the forehead of a user in a binaural test mode;

Fig. 7 is a view of the hearing evaluation device being incorrectly positioned out of range and oriented at an unacceptable incidence angle with respect to the forehead of a user in a binaural test mode;

10 **Fig. 8** is a view of the hearing evaluation device being correctly positioned at 0° degree incidence angle with respect to an ear of a user in a monaural test mode;

Fig. 9 is a view of the hearing evaluation device also being correctly positioned at 45° degree incidence angle with respect to an ear of a user in an alternate monaural test mode;

15 **Fig. 10** is a view of the hearing evaluation device of the present invention connected to an auxiliary instrument;

Fig. 11 is a view of the hearing evaluation device held by a test operator directing the speaker at a test subject; and

Fig 12 is an embodiment of the hearing evaluation device incorporating a control magnet within its housing to remotely control the function of a hearing aid worn in the ear
20 canal.

Detailed Description of the Preferred Embodiments and Methods

5 The present invention, shown in **Figures 1-12**, provides a personal hearing evaluation device **10** for accurately presenting multi-level acoustic test stimuli (sounds) to an individual via an audio transducer (i.e., speaker) **11** incorporated within the housing of the device. The
10 invented device **10**, as shown in **Figs. 1 and 2**, is designed for holding by hand and for directing sound **13** from its speaker **11** towards an ear **3** of a user **1** in a contactless manner but within the direct sound field range of the speaker. In the preferred embodiments, shown in **Figs. 1-11**, the device **10** comprises a position sensor **12** for automatically measuring the position of the device **10** with respect to the user's head **4**, or a part thereof of interest, depending on the test
15 mode as described below. The device **10** also comprises keys (switches, e.g., **61** and **62**, **Fig. 2**) for selecting at least two levels of sound **13**, presented in the direction of an ear (monaural mode, **Figs. 8 and 9**) or both ears (binaural mode, **Figs. 6 and 7**).

The position sensor **12** incorporated in the preferred embodiment of the invented device produces incidence wave **14** (solid arrows) which partially bounces off the head, or a part
20 thereof (i.e., nose, forehead, chin, ear, etc.), and becomes a reflected wave **15** (dashed arrows) for reception by the position sensor **12**. The position sensor **12** in the preferred embodiment comprises one or more ultrasonic transducers. **Fig. 3** shows a position sensor **12** employing a pair of ultrasonic transducers. The first transducer is a transmitter **20** for emitting incident wave **14**, and second transducer is a receiver **22**, for receiving the reflected wave **15** bouncing
25 off the head or a part thereof. The transmitter **20** and receiver **22** transducers further employ directional filters, **21** and **23**, respectively, for appropriately directing the incident wave **14** and

receiving reflected wave 15. These filters improve the reception and directionality of the position sensing process for ensuring proper positioning of the device with the respect to the individual.

In a preferred embodiment of the position sensor, shown in Fig. 4, a unitary ultrasonic transducer 12 (for example, piezoelectric transducer model ITC-9073 manufactured by International Transducer Technology, Inc.) is employed both for transmitting incident wave 14 and for receiving reflected wave 15. This unitary transducer design consumes less space and thus is more suited for the miniature battery-operated design of the hearing evaluation device of the invention.

Figure 5 shows a block diagram of an exemplary embodiment of the personal hearing evaluation device 10. A controller 30 (i.e., microprocessor, microcontroller, etc.) is employed to perform various computational and control processes as will be described below. Memory 50 is employed to store program data (not shown) and test stimulus data (51 and 52) in digital format representative of acoustic test stimuli to be presented by the speaker 11 upon request by the test subject 1 or a test operator 8 (Fig. 11). Test stimulus data may be representative of speech words 51 (Fig. 5), noise 52 and any other signal which is of audiological significance (not shown) such as pure tone, warble tone, chirp, etc. Test stimulus data is retrievable from memory 50 by the controller 30 for conversion into analog signal 41 by the digital to analog (D/A) converter 40. The analog signal 41 is then delivered to a programmable volume control 42 and then to a power amplifier 43 for providing speaker input signal 44 to the speaker 11. Test sound 13 is finally produced by speaker 11 and directed towards the test subject 1

positioned in the direct sound field range as shown in **Fig. 1**.

The block diagram of **Fig. 5** also shows position sensor **12** (an ultrasonic transducer) which transmits ultrasonic incident wave **14** and receives ultrasonic reflected wave **15** from the head or the ear of a test subject **1** (**Fig. 1**). The controller **30** is also connected to transmission
5 circuitry **31** (labeled TRX circuitry in **Fig. 5**) and reception circuitry **32** (labeled RX circuitry in **Fig. 5**) for processing of signals sent and received during the process of position sensing. The microcontroller **30** is also connected to a switch array **60** (switches, keys, etc.) for selecting and presenting acoustic stimuli upon the request of a test subject **1** or a test operator **8** (**Fig. 11**).

10 A typical cycle for the position sensing process is automatic and begins when the controller **30** receives an actuation signal from a key (part of the switch array **60**). The appropriate pattern of initial transmission signal **33** is produced by the controller **30** and fed into the transmission circuitry **31** which produces an output transmission signal **35** causing the position sensor **12** to transmit an ultrasonic incident wave **14** towards the head or ear of the test
15 subject. A properly positioned head or ear with respect to the device will cause a reflected wave **15** to be received by the position sensor **12**, which produces incoming reception signal **36**. Reception circuitry **32** processes the incoming reception signal **36** and delivers a filtered reception signal **37** to controller **30**. The latency period -- the time between the onset of signal transmission and reception -- is employed by the controller **30** to compute the position of head
20 or ear with respect to the device **10**. The above mentioned process is typically performed in repeated bursts or packets of sensing signals, according to an appropriate detection algorithm,

for determining the correct position of the device in the presence of possible noise and interference.

Upon proper positioning of the device by the position sensor system (in **Fig. 5** comprising ultrasonic transducer position sensor **12**, transmission circuitry **31**, reception circuitry **32** and microcontroller **30**), the device **10** delivers an acoustic test stimuli via speaker **11** to the test subject **1**. It will be understood, of course, that although the incident wave **14** delivered by position sensor **12** and the test stimulus delivered via speaker **11** to the test subject appear to be directed in opposite directions in the block diagram of **Fig. 5**, this is simply for the sake of convenience of block diagrammatic representation and they are actually delivered in the same general direction as indicated in **Figs. 1** and **2**. The automatic position sensing process is relatively rapid and typically occurs within 100 milliseconds (ms) after pressing a stimulus request key. Therefore, the onset of a test stimulus is essentially perceived "instantaneously" by a test subject.

However, if the positioning of the head is determined improper by the position sensor system (i.e., out of range, improper orientation, reverberant environment, etc.), the device presents the appropriate alarm indicator to the user. **Fig. 2** for example shows an alarm light indicator **71** in the form of an LED (light emitting diode). Alternatively, a LCD (liquid crystal display) or even distinct audible sounds (i.e., buzzer-like) may be employed to alert the user of an improper positioning or function of the invented device. Display elements are collectively shown as LED/Display **70** in **Fig. 5**.

The device in the embodiment shown in **Fig. 5** also incorporates a microphone **16** for

65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285

accommodate the arm length range of individuals holding the device as shown in **Figs. 1 and 2.**

Figure 7 shows an example of a binaural test mode with device **10** being incorrectly positioned outside the proper range **60** and also being incorrectly oriented with respect to the forehead **4** of the user **1**. Since the incident angle θ (**61**) is much greater than 0° degree, the incident wave is minimally reflected, if at all. However, even if a fringe incident wave **14'** is reflected causing a fringe reflected wave **15'**, the reception signal **37** is insufficiently weak as determined by the position sensor system.

In the binaural test mode, shown in **Figs. 6** (correct) and **7** (incorrect), both ears are typically involved in the hearing evaluation process. However, if only a single ear is to be tested in this mode, the other ear must be excluded by an appropriate method such as by occluding the non-test ear or by turning off a hearing aid worn in the non-test ear.

Fig. 8 shows a preferred method for monaural hearing evaluation. The invented device **10** is placed within exceptional proximity to a single test ear **3** (right). In this monaural test mode, the device is placed within a 2-10 cm range from the ear and oriented at incidence range of $0^\circ - 45^\circ$ degrees. **Fig. 8** shows device placement at 0° degree incidence with respect to right ear **3**. **Fig. 9** shows device placement at 45° degrees incidence with respect to a left ear **3'**.

Fig. 2 shows a perspective view of an exemplary embodiment of the hearing evaluation device **10** being held by hand **5** of a test subject (**1** in **Fig. 1**). The device **10** comprises a first key **61** configured for pressing by the thumb **6** and a second key **62** configured for pressing by the index finger **7**. The speaker **11** is oriented towards one or both ears as shown in **Figs. 6-9**

and described above. Light Emitting Diodes (LED), 71 and 72, are employed to provide visual indications to the test subject 1. For example, an alarm LED 71 (typically a red light) is provided to indicate incorrect positioning of the device. LED 72 (typically a green light) may be used to indicate valid "OK" operation or charged battery. A directional filter 21 is fitted
5 over the position sensor 12 to improve the directionality of incident wave 14, reflected wave 15, or both. A speaker cover 45 with holes 46, or an acoustically transparent structure (not shown), are provided to protect the speaker 11 within while allowing test sound 13 to pass through towards the test subject.

Fig. 2 also shows a first switch 25 (two-position switch) for selecting one of two signal
10 types; speech (marked SP) or narrow-band-noise (marked NBN). A second switch 26 (three-position switch) provides selection of one of three frequency bands; low, medium or high (labeled LF, MF and HF, respectively). Keys, 61 and 62, are employed to select at least two levels of sounds. In the preferred embodiment, these two keys present soft and comfortable sound levels, both with respect to normal hearing individuals. Soft sound key 62, for example,
15 (marked "S") preferably presents a fixed level sound in the range of 20 to 40 dB HL (hearing level). Comfortable sound key 61, for example, (marked "C") preferably presents a fixed level sound in the range of 45 to 60 dB HL.

The exemplary key and switch configuration of the device 10 in Fig. 2 leads to a combination of 12 individual test stimuli (2 keys x 2 positions x 3 positions) for performing
20 various hearing evaluation tests. The accuracy of each test stimuli presented is ensured and regulated by the position sensor system incorporated within as described above. For example,

if the speaker-head distance is measured (automatically) to be at 50 cm (i.e., binaural test mode), the speaker input signal 44 (Fig. 5) is then automatically reduced relative to a condition where the speaker-ear distance is at 5 cm (i.e., monaural test mode). This automatic adjustment (auto-calibration) is necessary in order to produce an equal perception of loudness at the ear, irrespective of the test mode or the exact position of the speaker 11.

In addition to the automatic level adjustment affecting the speaker input signal, the frequency characteristics of the test sound may also be manipulated in order to minimize inaccuracies associated with frequency-dependent stimulus. In pure tone test sounds, for example, it may be desirable to slightly shift the test frequency in order to minimize the affects of standing waves. A slight shift in the frequency is considered acceptable in audiological standards for most audiometric evaluations. For example, $\pm 1\%$ and $\pm 3\%$ frequency variation is permissible for type 1 and type 4 audiometers, respectively, according to ANSI S3.6, 1996.

The types of test signals possible with the present invention are not limited to speech, pure tones or narrow-band-noise. Virtually any signal of audiological significance may be reproduced from a digital recording, or synthesized, by the microcontroller for the presentation to the test subject. Other possible signal types include warbled tones, white noise, chirp (sine-wave composition), speech noise and other frequency weighted signals.

The hearing evaluator of the present invention, although miniature and employing a miniature audio transducer (speaker) 11, can produce sound at significant intensity levels when positioned within close proximity to a test ear as shown in Figs 8 and 9. In this monaural test mode, the intensity levels of test stimuli at the ear can reach 90 dB-SPL (sound pressure level)

or more while consuming little energy available from standard batteries. For example, a 98.3 dB-SPL tone at 4000 Hz. was produced at the ear from a miniature high fidelity speaker (model 4D06C manufactured by Panasonic) when positioned approximately 5 cm from an individual's ear (monaural test mode Fig. 8). The speaker input signal voltage to produce the 98.3 dB at 5 cm was measured at 0.7 Vrms. The power into the speaker measured at about 0.05 watt, which is readily available from standard batteries. Loud level sounds at 90 dB-SPL are particularly useful in assessing the aided hearing function of an individual during the fitting process to ensure comfortable hearing when the hearing aid is subjected to loud sounds. If found too loud by the aided test subject, the maximum output of the hearing aid must be reduced to a more acceptable level.

The same speaker input signal level (0.7 Vrms) produced only 82.5 dB-SPL at the ear when the speaker was positioned at 40 cm. Obviously, by scaling down the speaker input signal, soft and even threshold level sounds can be readily produced at virtually any distance within the preferred usable range of 2 to 60 cm. The above sound pressure level measurements at the ear were taken by probe-tube microphone system (model ER-7C, manufactured by Etymotic Research).

The personal hearing evaluator device 10 can be used by a test subject 1 to conduct a self-administered screening evaluation (pass/fail test) using the keys provided on the device.

The device in the above-described preferred and alternate embodiments can also be used in a professional setup during the fitting process of a hearing aid. For example, in the unaided condition and prior to hearing aid selection, the threshold of hearing of an individual (test

subject) is determined at various audiometric frequencies. Later on, the hearing evaluation is performed while a hearing aid is *in situ* (worn in the ear or the ear canal). In this aided condition, adjustments to the in-situ hearing aid are made while the test subject responds to the sound field stimuli produced by the hand-held device of the present invention. For example, soft level gain, compression ratio, maximum output, frequency response, attack time and any other parameter of a hearing aid, may be adjusted based on the test sounds produced from the speaker of the hand-held device. Following the fitting process, the test subject can use the hearing evaluation device 10 as a personal hearing evaluator. For example the acuity of the aided hearing can be checked regularly by the user at home by pressing the soft level key (62 in Fig. 2) to present soft level sounds (audible by normal hearing individuals). This is important because hearing aids tend to gradually deteriorate with time due to moisture or earwax contamination. A regular check-up by the hearing evaluation device of the invention should detect possible changes in either the hearing aid or the hearing ability of the user.

In the above-described embodiments, the hand-held hearing evaluation device is described in stand-alone configurations for use in unaided or aided conditions. Fig. 10 shows an alternate embodiment of the device 10 connected to an auxiliary instrument 80 (shown as a computer or computer-based instrument). The elongated hand-held device 10 is provided with an interface port 28 (also shown in Figs. 2 and 5) for connecting to auxiliary instrument 80 via the connection cable 81 and its electrical plug 82 inserted into interface port 28 of the device 10. The auxiliary instrument 80 is used by a test operator to control the device 10 by sending the appropriate control commands to the controller 30 (Fig. 5) of the device via

auxiliary interface circuitry 48 (Fig. 5). This auxiliary control mode available by the present invention allows a test operator (other than the test subject holding the device 10) to remotely control the function of the device 10. One advantage of this mode is to allow the operator to select a test stimulus from a broader range than possible with the device in its stand-alone configuration (having relatively a limited number of key and switch selection). The remote control interface mode is useful, for example, in performing a more comprehensive hearing evaluation such as for conducting a complete audiogram test involving 6 or more frequencies. In the remote control mode by an auxiliary instrument 80, a key (such as key 61 or key 62) within the device 10 can be used as a response key to register responses of the test subject and relay such registration to auxiliary instrument 80 when the test subject hears and presses the response key.

The auxiliary instrument 80, in conjunction with a response key on the device, can be used to automate the presentation of a hearing test according to procedures and protocols known in the field of automated audiometry. Furthermore, the auxiliary instrument 80 may be used to program the connected device 10 to perform specific test or function according to the needs of the individual test subject. The auxiliary instrument 80 may be a computer as shown, a microprocessor-based audiometer instrument (not shown), or any other suitable control instrument. The connection between the auxiliary instrument 80 and the device 10 may be via a direct wire as shown in Fig. 10, or via a wireless connection (not shown) as widely known in the field of wireless control and communications.

The auxiliary instrument mode is ideally suited during the initial fitting evaluation at the

site of the hearing aid dispensing professional. For example, a test operator (audiologist, doctor, nurse, etc.) can perform various unaided and aided evaluation on a test subject holding the device by hand. Once the hearing aid fitting process is completed, the hand-held device 10 is then disconnected from the auxiliary instrument 80 and offered to the test subject as a personal evaluator. Similarly, the personal evaluator device 10 can be used to regularly verify the proper function of an in-situ hearing device. The personal evaluator device 10 comprises a battery 27 for powering the device in its stand-alone mode after being disconnected from the auxiliary instrument 80.

The auxiliary instrument mode is also suited for remotely administering a hearing test when the subject is remotely present and the device is connected to the appropriate network. For example, a hand-held device 10 can be directly connected to a computer which is also connected to a remote computer (auxiliary instrument) via the Internet. This way, a hearing professional can remotely administer a test to a test subject, present at home for example. In this case, the test subject simply connects the hearing evaluation device 10 to a computer port (not shown) of a personal computer connected via the Internet to the computer of the hearing professional. Other remote interface methods are possible and conceivable as will become obvious to those skilled in the art of computers, communications and networking.

The invented device 10 is highly portable and configured for easy transport and convenient hand-held operation as described in the above embodiments. For example, the device in Fig. 2 is shown resembling a hand-held stopwatch or a garage-door opener. In Fig. 10 the device 10 is shown resembling a pen. Other designs, well within the scope of this

invention, include wristwatch **95** (**Fig. 13**) and other configurations, which will become obvious to those skilled in the art of miniature personal instrument design.

The invented device **10**, although most suitable for holding by a test subject who orients the speaker towards his or her own ears, it may be desirable in certain conditions for a test operator (a hearing professional, parent, spouse, etc.) to hold the device **10** and assist in conducting a hearing test. This may be necessary for testing young children, persons with poor dexterity, and other difficult to test individuals. **Fig. 11** shows a test operator **8** holding the hearing evaluation device **10**. Similarly, the test sound **13** and the incident wave **14** of the position sensor **12** are directed towards the head **3** of the test subject **1** to properly deliver acoustic test stimuli to one or both ears of the test subject **1**.

The personal hearing evaluator may incorporate wireless remote control means for remotely controlling or programming a hearing aid. For example, hearing aid volume can be remotely adjusted, or the power may be remotely turned on or off. Wireless control means are widely known in the field of hearing aids and include ultrasonic, electromagnetic, sonic, magnetic and infrared signals. In a preferred embodiment shown in **Fig. 12**, the hearing evaluator device **10** comprises a magnet **18** having a magnetic field **19** which remotely, but within close proximity, controls a hearing aid **90** positioned in the ear canal **7**. The magnetic field **19** may be reversed in its direction (not shown) simply by flipping the device and thus reversing the polarity of the magnet **18** within. The details of such magnetic control operation are disclosed in a pending patent application Serial No. 09/181,533 of the same inventor, filed October 28, 1999 and incorporated herein by reference. The magnet typically employed within

a speaker 11 transducer may be relied on for such remote control application thus eliminating the need for an additional magnet.

The position sensor system in the preferred embodiments, described above, employ ultrasonic transduction for sending and receiving ultrasonic waves. However, other
5 contactless position sensing means are possible and may be equally suitable as known by those skilled in the art of proximity and position sensing. For example by employing optical transducers (i.e., infrared LED) in conjunction with appropriate directional optical filters. In another example, a sonic wave produced by the speaker 11 may be utilized for position sensing.

Although a presently contemplated best mode of practicing the invention has been
10 described herein with reference to certain presently preferred and alternate embodiments and methods of use, it will be recognized by those skilled in the art to which the invention pertains from a consideration of the foregoing description, that variations and modifications of these exemplary embodiments and methods may be made without departing from the true spirit and scope of the invention. Thus, the above described embodiments of the invention should not be
15 viewed as exhaustive or as limiting the invention to the precise configurations or techniques disclosed. Rather, it is intended that the invention shall be limited only by the appended claims and the rules and principles of applicable law.

WHAT IS CLAIMED IS:

1 1. A device for performing sound field hearing testing, said device comprising:
2 a) an audio transducer for producing acoustic test stimuli to a test subject within
3 the direct sound field range of said audio transducer, and
4 b) a contactless position sensor system for measuring the position of said device
5 with respect to the head or part thereof of interest of said test subject,
6 whereby hearing evaluation of said test subject, when properly positioned relative
7 to said device, may be performed by said device based on said acoustic test stimuli.

1 2. The device of claim 1, including means for automatically determining or
2 adjusting characteristics of said acoustic test stimuli, including onset, amplitude and frequency
3 characteristics, in response to position measurements performed by said position sensor system.

1 3. The device of claim 1, wherein said device is constructed and adapted to be
2 hand held by said test subject.

1 4. The device of claim 1, wherein said device is configured as a wrist watch.

1 5. The device of claim 1, wherein said device is configured for operation by a test
2 operator assisting said test subject.

3 individuals.

1 13. The device of claim 12, wherein said comfortable level listening range is
2 between 45 and 65 dB HL.

1 14. The device of claim 1, wherein said contactless position sensor system
2 comprises at least one of an optical transducer, acoustic transducer and ultrasonic transducer.

1 15. The device of claim 1, wherein said contactless position sensor system
2 comprises means for automatically computing the distance between said device and the head
3 or part thereof of interest of said test subject.

1 16. The device of claim 1, wherein said contactless position sensor system
2 comprises means for automatically determining if the device is within an operable range and
3 orientation with respect to the head or part thereof of interest of said test subject.

1 17. The device of claim 1, wherein said contactless position sensor system
2 comprises a transmitting transducer and a receiving transducer.

1 18. The device of claim 17, wherein said contactless position sensor system
2 comprises means for computing the distance between the device and the head or said part

06122017

1 **25.** The device of claim **23**, wherein said interface means comprise an electrical
2 cable.

1 **26.** The device of claim **23**, wherein said interface means comprise the Internet.

1 **27.** The device of claim **23**, wherein said interface means comprise a wireless link
2 including any of infrared, radio frequency, electromagnetic, sound, or ultrasound.

1 **28.** The device of claim **23**, further comprising response registration means for
2 registering test responses by said test subject and relaying said test responses to said remote
3 instrument.

1 **29.** The device of claim **28**, wherein said response registration means comprise at
2 least one key.

1 **30.** The device of claim **1**, further comprising visual status display means, including
2 liquid crystal display (LCD) and light emitting diode (LED).

1 **31.** The device of claim **1**, further comprising a controller.

1 **32.** The device of claim **1**, further comprising memory for storage of data

6514263-123456789

2 representative of acoustic test stimuli.

1 33. The device of claim 1, further comprising a microphone.

1 34. The device of claim 33, wherein said microphone provides means for measuring
2 ambient background noise, for self testing, or for self calibration of said device.

1 35. The device of claim 7, further comprising wireless remote control means for
2 controlling or adjusting at least one parameter of said hearing aid worn by said test subject.

1 36. The device of claim 35, wherein said wireless remote control means comprise
2 a magnet.

1 37. A hand held device for performing sound field hearing evaluation in a
2 contactless manner with respect to a test ear of a test subject, said device comprising:

3 a) an audio transducer for delivering acoustic test stimuli to said test subject
4 holding said device within the direct sound field range of said audio transducer,

5 b) means for selecting delivery of said acoustic test stimuli through said audio
6 transducer at two or more intensity levels for performing one or more supra-threshold hearing
7 measurements, and

8 c) means for selecting delivery of said acoustic test stimuli through said audio

9 transducer in at least two frequency ranges for performing hearing evaluation in at least two
10 frequency ranges.

1 38. The hand held device of claim 37, wherein said device is configured for
2 operation by said test subject.

1 39. The hand held device of claim 37, wherein said device is configured for
2 operation by a test operator assisting said test subject

1 40. The hand held device of claim 37, including means for performing said hearing
2 evaluation in an unaided condition in which said test subject is not wearing a hearing aid.

1 41. The hand held device of claim 37, including means for performing said hearing
2 evaluation in an aided condition in which said test subject is wearing a hearing aid.

1 42. The hand held device of claim 41, including means for performing said hearing
2 evaluation in said aided condition to verify functionality of said hearing aid worn by said test
3 subject.

1 43. The hand held device of claim 41, including means for performing said hearing
2 evaluation in said aided condition to adjust at least one parameter of said hearing aid.

051250-1310450

1 **44.** The hand held device of claim **37**, further comprising means for delivering at
2 least one of said acoustic test stimuli within the soft level listening range of normal hearing
3 individuals.

1 **45.** The hand held device of claim **44**, wherein said soft level listening range is
2 between 20 and 40 dB HL.

1 **46.** The hand held device of claim **37**, further comprising means for delivering at
2 least one of said acoustic test stimuli within the comfortable level listening range of normal
3 hearing individuals.

1 **47.** The hand-held device of claim **46**, wherein said comfortable level listening range
2 is between 45 and 65 dB HL.

1 **48.** The hand held device of claim **37**, further comprising a contactless position
2 sensor system for measuring the position of said device with respect to the head or part thereof
3 of interest of said test subject.

1 **49.** The hand held device of claim **48**, further including means for automatically
2 adjusting the characteristics of said acoustic test stimuli, including onset, amplitude and

3 frequency, in response to position measurements performed by said contactless position sensor
4 system.

1 50. The hand held device of claim 48, wherein said contactless position sensor
2 system comprises at least one ultrasonic transducer.

1 51. The hand-held device of claim 48, wherein said contactless position sensor
2 system comprises means for automatically determining if the device is within an operable
3 distance and orientation with respect to said head or part thereof of interest of said test subject.

1 52. The hand held device of claim 48, wherein said contactless position sensor
2 system comprises means for computing the distance between the device and said head or part
3 thereof of interest of said test subject based on the latency period between a transmitted signal
4 emitted by an ultrasonic transmitting transducer and reflected signal received by an ultrasonic
5 receiving transducer.

1 53. The hand held device of claim 37, further comprising means to select from at
2 least two types of said acoustic test stimuli including speech, noise and tone types.

1 54. The hand held device of claim 37, further comprising means to select said
2 acoustic test stimuli in at least two frequency ranges.

Attorney for Plaintiff

1 **55.** The hand held device of claim **37**, further comprising at least one switch for
2 selection of said acoustic test stimuli.

1 **56.** The hand held device of claim **37**, further comprising interface means for
2 connecting a remote instrument for remotely operating said hand held device.

1 **57.** The hand held device of claim **56**, wherein said remote instrument comprises a
2 computer.

1 **58.** The hand held device of claim **56**, wherein said interface means comprise the
2 Internet.

1 **59.** The hand held device of claim **56**, wherein said interface means comprise an
2 electrical cable.

1 **60.** The hand held device of claim **56**, wherein said interface means comprises a
2 wireless link including any of infrared, radio frequency, electromagnetic, sound, or ultrasound.

1 **61.** The hand held device of claim **56**, further comprising response registration
2 means for registering test responses by said test subject and relaying said test responses to said

3 remote instrument.

1 **62.** The hand device of claim **61**, wherein said response registration means comprise
2 at least one key.

1 **63.** The hand held device of claim **37**, further comprising visual status display
2 means, including an liquid crystal display (LCD) and light emitting diode (LED).

1 **64.** The hand held device of claim **37**, further comprising a controller.

1 **65.** The hand held device of claim **37**, further comprising memory for storage of
2 data representative of acoustic test stimuli.

1 **66.** The hand held device of claim **37**, further comprising a microphone.

1 **67.** The hand held device of claim **66**, wherein said microphone provides means for
2 measuring ambient background noise, for self testing, or for self calibration of said device.

1 **68.** The hand held device of claim **41**, further comprising wireless remote control
2 means for controlling or adjusting at least one parameter of said hearing aid worn by said test
3 subject.

094001-1310460

1 **69.** The hand held device of claim **68**, wherein said wireless remote control means
2 comprise a magnet.

1 **70.** A system for performing hearing evaluation of a test subject comprising:

2 a) a hand held device containing an audio transducer within, said hand held device
3 being positioned within the direct sound field range of said audio transducer and positioned in
4 a contactless manner with respect to a test ear of said test subject,

5 b) an auxiliary instrument operably connected to said hand held device for remotely
6 controlling the operation of said hand held device, and

7 c) means for selecting the delivery of acoustic test stimuli through said audio
8 transducer at two or more intensity levels and at two or more frequency ranges.

1 **71.** The system of claim **70**, wherein said hand held device is independently operable
2 as a hearing evaluator when detached from said auxiliary instrument.

1 **72.** The system of claim **70**, wherein said hand held device further comprises a
2 contactless position sensor system for measuring the position of said hand held device with
3 respect to the head or part thereof of interest of said test subject.

1 **73.** The system of claim **72**, including means for automatically adjusting the

10 c) delivering said acoustic test stimuli to said test subject while said device is
11 oriented toward said subject's head or part thereof of interest.

1 85. The method of claim 84, including the step of orienting said audio transducer
2 at approximately 0° degree incidence and within a distance range of 30-60cm with respect to
3 the forehead of said test subject, while performing said step of delivering acoustic test stimuli.

1 86. The method of claim 84, including the step of orienting said audio transducer
2 at approximately 0° - 45° degree incidence range and within a distance range of 2-10 cm with
3 respect to a test ear of said test subject while performing said step of delivering acoustic test
4 stimuli, for monaural hearing evaluations.

1 87. The method of claim 84, including delivering said acoustic test stimuli in an
2 unaided condition in which said test subject is not wearing a hearing aid.

1 88. The method of claim 84, including delivering said acoustic test stimuli in an
2 aided condition in which said test subject is wearing a hearing aid.

1 89. The method of claim 88, including delivering said acoustic test stimuli in said
2 aided condition to verify the functionality of said hearing aid.

1 **90.** The method of claim **88**, including delivering said acoustic test stimuli in said
2 aided condition to adjust at least one parameter of said hearing aid.

1 **91.** The method of claim **84**, wherein said device is hand held by said test subject
2 during said hearing evaluation.

1 **92.** The method of claim **84**, wherein said device is worn as a wrist watch by said
2 test subject during said hearing evaluation.

1 **93.** The method of claim **84**, wherein said device is configured to be held by a test
2 operator assisting said subject during said hearing evaluation.

1 **94.** The method of claim **84**, including connecting a remote instrument to said
2 device via an interface to remotely control said device during said hearing evaluation.

1 **95.** The method of claim **94**, including connecting said remote instrument to said
2 device via the Internet.

1 **96.** The method of claim **94**, wherein said remote instrument is a computer.

1 **97.** The method of claim **94**, wherein said remote instrument is an audiometer.

66160-15100-00

1 **103.** The method of claim **102**, including performing said hearing evaluation in said
2 aided condition to verify the functionality of said hearing aid.

1 **104.** The method of claim **102**, including performing said hearing evaluation in said
2 aided condition to adjust at least one parameter of said hearing aid.

1 **105.** The method of claim **98**, in which a test operator holds said device while
2 assisting said individual in said hearing evaluation.

1 **106.** The method of claim **98**, including connecting a remote instrument to said
2 device via an interface to remotely control said device during said hearing evaluation.

1 **107.** The method of claim **106**, including connecting said remote instrument to said
2 device via the Internet.

1 **108.** The method of claim **106**, wherein said remote instrument is a computer.

1 **109.** The method of claim **106**, wherein said remote instrument is an audiometer.

PERSONAL HEARING EVALUATOR

ABSTRACT OF THE DISCLOSURE

A hand-held device includes an audio transducer (i.e., speaker) for delivering acoustic
5 test stimuli to a test subject within the direct sound field range of the device. The device
accurately delivers multi-level and multi-frequency test stimuli for the subjective response by
the test subject holding the device. An ultrasonic position sensor within the device determines
the position of the device with respect to the head or a portion of interest of the head of the test
subject while the device is being held. The acoustic test stimuli are controlled and regulated
10 based on the position of the device with respect to the test subject so that accurate levels of test
stimuli are presented only when the device is within a proper range and irrespective of its exact
position with respect to the test subject's head.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6


[illegible]

Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13

In re Application of:

Group Art Unit: _____

Examiner: _____

Title: PERSONAL HEARING EVALUATOR

As the below named inventor, I hereby declare that:

This declaration is made in an original application for utility patent.

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention set forth above, the specification of which is being filed in the Patent and Trademark Office herewith.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims thereof.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, section 1.56(a).

As the named inventor, I hereby appoint Donald R. Greene, Reg. No. 22,470, as attorney to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith.

Direct telephone calls to:

Donald R. Greene
Post Office Box 12995
Scottsdale, AZ 85267-2995

Donald R. Greene
Tel: 480-488-9895
Fax: 480-488-5654

Declaration

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Signature

Full name of sole inventor: Adnan Shennib

Inventor's signature Adnan Shennib

Date 9/20/99

Country of Citizenship: United States of America

Residence: Fremont, California

Post Office Address: 34337 Xanadu Terrace
Fremont, California 94555